

# SPECIFICATIONS

## PRODUCT OVERVIEW



### NovaBlade Flush Mount Frame

The flush mount frame brings the T-bar fit into plasterboard ceilings. It's the neatest way to have great light on hand without a luminaire in sight. It fits flush with the ceiling and requires as little as 150mm clearance in the ceiling. Once installed, the NovaBlade just drops in as with a T-Bar ceiling grid.



### NovaBlade Surface Mount Frame

The surface mount frame is suitable for installation on hard surfaces or spaces with no recessing space. Only 50mm deep to house the panel and driver internally, the design of the frame provides easy installation and minimal aesthetic intrusion.



### NovaBlade Semi Flush Mount Frame

The semi-flush mount is for those more awkward places where structural or other considerations make flush mounting impossible. Just mount the base, insert the NovaBlade and close the patented sliding gate. The finished result is a protrusion of only 15mm.



### NovaBlade Pendant Mount Kits

Suspended mounting is sometimes a good option for task areas or high ceilings.

Standard hanger cable length is 1.2M. Longer lengths available to special order.

Part No	Size
LL9P63FK	595 x 295mm
LL9P66FK	595 x 595mm
LL9P123FK	1195 x 295mm
LL9P126FK	1195 x 595mm

Part No	Size
LL9P33SK	595 x 295mm
LL9P66SK	595 x 595mm
LL9P123SK	1195 x 295mm
LL9P126SK	1195 x 595mm

Part No	Size
LL9P63SFK	595 x 295mm
LL9P66SFK	595 x 595mm
LL9P123SFK	1195 x 295mm
LL9P126SFK	1195 x 595mm

Part No	Size
LL9PSUSP	1.2m Suspension

Note: The opening requires timber framing to meet building regulations.