



led lighting product catalogue

2022



contents

vue micro	3
silver XS	4
silver S	5
silver S TW	6
silver M	7
silver M TW	8
preneo	9
smooth S	10
smooth M	11
smooth L	12
polo	13
hellion	14
artere 1010	15
artere 1617	18
ligne-micro	20
teso basic 15W	21
teso basic 26W	22
teso pro	23
surface track accessories	24
recessed track accessories	26
cortile	28
iugis	29

micro

vue series




the vue micro range is suitable for residential, retail or commercial projects. Tiny 33mm pin points of light that are discrete yet effective, with options from 15° up to 40°, and a wall-washer reflector. The Vue Micro ELG adjustable 6W has a deepset light source with a black reflector to eliminate glare and provide a tilt of up to 25°.

specifications

system wattage:	2W, 6W, 8W
CCT:	2700K, 3000K, 4000K
luminaire output:	213lm up to 615lm
beam angles:	15°, 30°, 40°, wall-wash (adjustable 15°, 25°, 40°)
CRI:	>90
Macadam:	3 SDCM
control:	non-dim, 1-10V, Triac, DALI, Casambi
cutout:	30mm
lifetime:	50,000hrs
build:	die-cast aluminium, reflector or lens
IP Rating:	IP20
warranty:	5 years
colours:	black and white
accessories:	honeycomb filter, clear lens, frosted lens
options:	extra low glare adjustable



dimensional drawings



product code

product group	group destination	wattage	dimmable	beam angle	colour temperature	fixture colour	mounting
FV vue	M micro	2 2W 6 6W 8 8W	Do non-dim D1 1-10V D2 TRIAC DD DALI CS Casambi	15 15° 30 30° 40 40° WW wallwash	27 2700K 30 3000K 40 4000K	W white B black	R recessed
FV vue	MV micro adjustable	6 6W	Do non-dim D1 1-10V D2 TRIAC DD DALI CS Casambi	15 15° 25 25° 38 38°	27 2700K 30 3000K 40 4000K	W white B black	R recessed



+61 (03) 9790 8999
lighting@verbatim.com.au
www.verbatimlighting.com.au



silver XS


vue series



architectural lighting requires the right luminaire. Highlighting and accenting with multiple sources rather than just flooding an area with light. The silver XS has a subtle aperture to minimise visual impact, and with an adjustable specular aluminium reflector and a range of beam angles to create the perfect effect.

specifications

system wattage	7W
CCT	2700K, 3000K, 3500K, 4000K
luminaire output	505lm - 562lm
beam angles	20°, 35°, 55°
CRI	90
Macadam	3 SDCM
control	on/off, triac, 1-10V, DALI, Casambi
cutout	Ø46mm for 5-25mm ceiling thickness
lifetime	50,000hrs
build	die-cast aluminium & specular aluminium reflector
IP rating	IP20
warranty	5 years
accessories	black or white trim honeycomb filter frosted diffuser



product code

FV	-	SXS	-	7	-	x	-	x	-	x	-	x	-	R
product group		group destination		wattage		dimmable		beam angle		cct		fixture colour		mounting
FV vue		SXS silver XS		7 7W		D0 non-dim D1 1-10V D2 TRIAC DD DALI CS Casambi		20 20° 35 35° 55 55°		27 2700K 30 3000K 35 3500K 40 4000K		W white B black		R recessed



+61 (03) 9790 8999
lighting@verbatim.com.au
www.verbatimlighting.com.au



silver S


vue series



architectural lighting requires the right luminaire. Highlighting and accenting with multiple sources rather than just flooding an area with light. The silver S has an adjustable specular aluminium reflector and a range of beam angles and washers to create the perfect effect. The range also includes a square trim and trimless options in both square and round trim.

specifications

system wattage	15.5W	
CCT	2700K, 3000K, 3500K, 4000K	
luminaire output	1103lm - 1229lm	
beam angles	25°, 38°, 55°, wallwash 16° at 8W system wattage	
CRI	90	
Macadam	3 SDCM	
control	on/off, triac, 1-10V, DALI, Casambi	
cutout	Ø63mm for 5-25mm ceiling thickness	
lifetime	50,000hrs	
build	die-cast aluminium & specular aluminium reflector	
IP rating	IP20	
warranty	5 years	
accessories	honeycomb filter clear lens frosted diffuser	options black or white trim square trimless specular, frosted or gold reflector



product code

FV	-	SS	-	15	-	x	-	x	-	x	-	x	-	R
product group		group destination		wattage		dimmable		beam angle		cct		fixture colour		mounting
FV vue		SS silverS		15 15.5W		D0 non-dim D1 1-10V D2 TRIAC DD DALI CS Casambi		25 25° 35 38° 55 55° WW wallwash		27 2700K 30 3000K 35 3500K 40 4000K		W white B black		R recessed



+61 (03) 9790 8999
lighting@verbatim.com.au
www.verbatimlighting.com.au



silver S TW


vue series



architectural lighting requires the right luminaire. Highlighting and accenting with multiple sources rather than just flooding an area with light. The silver S TW has an adjustable specular aluminium reflector and a range of beam angles and washers to create the perfect effect. The range also includes a square trim and trimless options in both square and round trim, and all with the flexibility to adjust the colour temperature between 2700K and 6500K.

specifications

system wattage	8.7W		
CCT	tuneable white - 2700K - 6500K		
luminaire output	572lm - 679lm		
beam angles	16°, 25°, 38°, 55°, wallwash		
CRI	90		
Macadam	3 SDCM		
control	DALI, Casambi		
cutout	Ø63mm for 5-25mm ceiling thickness		
lifetime	50,000hrs		
build	die-cast aluminium & specular aluminium reflector		
IP rating	IP20		
warranty	5 years		
accessories	black or white trim honeycomb filter clear lens frosted diffuser	options	black or white trim square trimless specular, frosted or gold reflector



product code

FV	SS	8	X	X	TW	X	S
product group	group destination	wattage	dimmable	beam angle	cct	fixture colour	mounting
FV Vue	SS silver S TW	8 8.7W	DD DALI CS Casambi	16 16° 25 25° 38 38° 55 55° WW wallwash	TW tuneable white	W white B black	R recessed



+61 (03) 9790 8999
lighting@verbatim.com.au
www.verbatimlighting.com.au



silver M


vue series



architectural lighting requires the right luminaire. Highlighting and accenting with multiple sources rather than just flooding an area with light. The silver S has an adjustable specular aluminium reflector and a range of beam angles and washers to create the perfect effect. The range also includes a square trim and trimless options in both square and round trim.

specifications

system wattage	31W		
CCT	2700K, 3000K, 3500K, 4000K		
luminaire output	2375lm - 2646lm		
beam angles	16°, 25°, 38°, 55°, wallwash		
CRI	90		
Macadam	3 SDCM		
control	on/off, triac, 1-10V, DALI, Casambi		
cutout	Ø103mm for 5-25mm ceiling thickness		
lifetime	50,000hrs		
build	die-cast aluminium & specular aluminium reflector		
IP rating	IP20		
warranty	5 years		
accessories	honeycomb filter clear lens frosted diffuser	options	black or white trim square trimless specular, frosted or gold reflector



product code

FV	-	SM	-	31	-	X	-	X	-	X	-	X	-	R
product group		group destination		wattage		dimmable		beam angle		cct		fixture colour		mounting
FV vue		SM silver M		31 31W		D0 non-dim D1 1-10V D2 TRIAC DD DALI CS Casambi		16 16° 25 25° 38 38° 55 55° WW wallwash		27 2700K 30 3000K 35 3500K 40 4000K		W white B black		R recessed



+61 (03) 9790 8999
lighting@verbatim.com.au
www.verbatimlighting.com.au



silver M TW

vue series




architectural lighting requires the right luminaire. Highlighting and accenting with multiple sources rather than just flooding an area with light. The silver S TW has an adjustable specular aluminium reflector and a range of beam angles and washers to create the perfect effect. The range also includes a square trim and trimless options in both square and round trim, and all with the flexibility to adjust the colour temperature between 2700K and 6500K.



specifications

system wattage	19,5W	
CCT	tuneable white - 2700K - 6500K	
luminaire output	1543lm - 1845lm	
beam angles	16°, 25°, 38°, 55°, wallwash	
CRI	90	
Macadam	3 SDCM	
control	DALI, Casambi	
cutout	Ø103mm for 5-25mm ceiling thickness	
lifetime	50,000hrs	
build	die-cast aluminium & specular aluminium reflector	
IP rating	IP20	
warranty	5 years	
accessories	honeycomb filter clear lens frosted diffuser	options black or white trim square trimless specular, frosted or gold reflector



product code

FV	SM	19	X	X	TW	X	S
product group	group destination	wattage	dimmable	beam angle	cct	fixture colour	mounting
FV Vue	SM silver M TW	19 19,5W	DD DALI CS Casambi	16 16° 25 25° 38 38° 55 55° WW wallwash	TW tuneable white	W white B black	R recessed



+61 (03) 9790 8999
lighting@verbatim.com.au
www.verbatimlighting.com.au



preneo


vue series

a high wattage solution suitable for high ceilings in open areas. A specular aluminium reflector minimises glare and the high CRI and tight colour consistency provides a maintained high quality light throughout the lifetime of the project.



specifications

system wattage	34W, 51W, 85W	
CCT	2700K, 3000K, 3500K, 4000K	
luminaire output	3148lm up to 7938lm	
beam angles	40°, 60°	
CRI	90	
Macadam	3 SDCM	
control	non-dim, 1-10V, DALI, Casambi	
cutout	Ø143mm or Ø183mm	
lifetime	50,000hrs	
build	die-cast aluminium, alu reflector	
IP rating	IP20/IP44	
warranty	5 years	
accessories	honeycomb filter clear lens frosted diffuser	options black or white trim



- HONEYCOMB
- CLEARLENS
- FROSTLENS



product code

FV	-	P	-	x	-	x	-	x	-	x	-	x	-	R
product group		group destination		wattage		dimmable		beam angle		cct		fixture colour		mounting
FV	vue	P	preneo	34 34W		D0 non-dim		40 40°		27 2700K		W white		R recessed
				51 51W		D1 1-10V		60 60°		30 3000K		B black		
				85 85W		D2 TRIAC				35 3500K				
						DD DALI				40 4000K				
						CS Casambi								



+61 (03) 9790 8999
lighting@verbatim.com.au
www.verbatimlighting.com.au



smooth S


vue series



a dark-light effect can create a soft and warm environment, and a curved edge transitions from light to dark gently. The overall effect being to draw the eye to the lit area or object. The Smooth range of architectural luminaires aims to provide the designer with the tools to create the perfect environment to connect with the end user.

specifications

system wattage	4W, 6W, or 8W
CCT	2700K, 3000K, 4000K, 5000K
luminaire output	380lm - 770lm
beam angles	15°, 24°, 38°
CRI	90
Macadam	3 SDCM
control	on/off, triac, 1-10V, DALI, Casambi
cutout	Ø40mm, for 5-25mm ceiling thickness
lifetime	50,000hrs
build	die-cast aluminium
IP rating	IP20
warranty	5 years
accessories	honeycomb filter clear lens frosted diffuser
options	black or white trim



product code

FV	-	SMS	-	x	-	x	-	x	-	x	-	R	
product group		group destination		wattage		dimmable		beam angle		cct		fixture colour	mounting
FV vue		SMS smooth S		4 4W 6 6W 8 8W		D0 non-dim D1 1-10V D2 TRIAC DD DALI CS Casambi		15 15° 24 24° 38 38°		27 2700K 30 3000K 40 4000K 50 5000K		W white B black	R recessed



+61 (03) 9790 8999
lighting@verbatim.com.au
www.verbatimlighting.com.au



smooth M



vue series



a dark-light effect can create a soft and warm environment, and a curved edge transitions from light to dark gently. The overall effect being to draw the eye to the lit area or object. The Smooth range of architectural luminaires aims to provide the designer with the tools to create the perfect environment to connect with the end user. Smooth is complimented with medium to large wattages and adjustable options.

specifications

system wattage	16W
CCT	2700K, 3000K, 3500K, 4000K
luminaire output	1573lm up to 1663lm
beam angles	15°, 25°, 40°, 60°
CRI	90
Macadam	3 SDCM
control	on/off, triac, 1-10V, DALI, Casambi
cutout	Ø78mm for fixed Ø92mm for adjustable
lifetime	50,000hrs
build	die-cast aluminium & specular aluminium reflector
IP rating	IP20/IP44
warranty	5 years
accessories	honeycomb filter options black or white trim clear lens frosted diffuser



product code

FV	SMM	16	X	X	X	X	R	F																																				
product group	group destination	wattage	dimmable	beam angle	colour temperature	fixture colour	mounting	tilt																																				
FV vue	SMM smooth m	16 16W	<table border="0"> <tr><td>Do</td><td>non-dim</td></tr> <tr><td>D1</td><td>1-10V</td></tr> <tr><td>D2</td><td>TRIAC</td></tr> <tr><td>DD</td><td>DALI</td></tr> <tr><td>CS</td><td>Casambi</td></tr> </table>	Do	non-dim	D1	1-10V	D2	TRIAC	DD	DALI	CS	Casambi	<table border="0"> <tr><td>15</td><td>15°</td></tr> <tr><td>25</td><td>25°</td></tr> <tr><td>40</td><td>40°</td></tr> <tr><td>60</td><td>60°</td></tr> </table>	15	15°	25	25°	40	40°	60	60°	<table border="0"> <tr><td>27</td><td>2700K</td></tr> <tr><td>30</td><td>3000K</td></tr> <tr><td>35</td><td>3500K</td></tr> <tr><td>40</td><td>4000K</td></tr> </table>	27	2700K	30	3000K	35	3500K	40	4000K	<table border="0"> <tr><td>W</td><td>white</td></tr> <tr><td>B</td><td>black</td></tr> </table>	W	white	B	black	<table border="0"> <tr><td>R</td><td>recessed</td></tr> </table>	R	recessed	<table border="0"> <tr><td>F</td><td>fixed</td></tr> <tr><td>A</td><td>adjustable</td></tr> </table>	F	fixed	A	adjustable
Do	non-dim																																											
D1	1-10V																																											
D2	TRIAC																																											
DD	DALI																																											
CS	Casambi																																											
15	15°																																											
25	25°																																											
40	40°																																											
60	60°																																											
27	2700K																																											
30	3000K																																											
35	3500K																																											
40	4000K																																											
W	white																																											
B	black																																											
R	recessed																																											
F	fixed																																											
A	adjustable																																											



+61 (03) 9790 8999
lighting@verbatim.com.au
www.verbatimlighting.com.au



smooth L


vue series



a dark-light effect can create a soft and warm environment, and a curved edge transitions from light to dark gently. The overall effect being to draw the eye to the lit area or object. The Smooth range of architectural luminaires aims to provide the designer with the tools to create the perfect environment to connect with the end user. Smooth is complimented with medium to large wattages and adjustable options.

specifications

system wattage	33W
CCT	2700K, 3000K, 3500K, 4000K
luminaire output	3148lm up to 3322lm
beam angles	15°, 30°, 60°
CRI	90
Macadam	3 SDCM
control	on/off, 1-10V, DALI, Casambi
cutout	Ø104mm
lifetime	50,000hrs
build	die-cast aluminium & specular aluminium reflector
IP rating	IP20/IP44
warranty	5 years
accessories	honeycomb filter options black or white trim clear lens frosted diffuser



product code

FV	-	SML	-	33	-	x	-	x	-	x	-	x	-	R	
product group	vue	group destination	smooth L	wattage	33W	dimmable		beam angle		cct		fixture colour		mounting	
FV	vue	SML	smooth L	33	33W	D0	non-dim	15	15°	27	2700K	W	white	R	recessed
						D1	1-10V	25	25°	30	3000K	B	black		
						D2	TRIAC	40	40°	35	3500K				
						DD	DALI	60	60°	40	4000K				
						CS	Casambi								



+61 (03) 9790 8999
lighting@verbatim.com.au
www.verbatimlighting.com.au



polo



vue series



The vue polo range is suitable for residential, retail or commercial projects. Surface mount downlight comes with specular finish glass reflector in aluminum vacuum coated and die cast aluminum housing, Citizen LED COB with 40° and 60° beam angle options,

specifications

system wattage:	10W, 20W
CCT:	2700k, 3000k, 3500k, 4000k
luminaire output:	1020k up to 2031m
beam angles:	40°, 60°
CRI:	>90
Macadam:	3 SDCM
control:	non-dim, Triac, DALI, 1-10V
diameter:	Ø122mm
lifetime:	50,000hrs
build:	die-cast aluminium, AL reflector
IP Rating:	IP20
warranty:	5 years
colours:	black and white
accessories:	ceiling bracket
options:	frosted glass, clear glass



product code

product group	group destination	wattage	dimming	beam angle	cct	fixture colour	mounting		
FV	Vue	P	Polo	10 10W 20 20W	D0 non-dim D1 1-10V D2 TRIAC DD DALI	40 40° 60 60°	27 2700K 30 3000K 35 3500K 40 4000K	W white B black	S Surface Mounted



+61 (03) 9790 8999
lighting@verbatim.com.au
www.verbatimlighting.com.au



hellion


vue series



The vue hellion range is suitable for residential, retail or commercial projects. Surface mount downlight comes with specular finish gloss reflector in aluminum vacuum coated and die cast aluminum housing, Citizen LED COB with 40° and 60° beam angle options,

specifications

system wattage:	20W, 33W, 45W
CCT:	2700k, 3000k, 3500k
luminaire output:	4000k 2062lm up to 4202m
beam angles:	40°, 60°
CRI:	>90
Macadam:	3 SDCM
control:	non-dim, Triac, DALI, 1-10V
diameter:	Ø150mm
lifetime:	50,000hrs
build:	die-cast aluminium, AL reflector
IP Rating:	IP65
warranty:	5 years
colours:	black and white
accessories:	ceiling bracket
options:	frosted glass



product code

FV	H	X	X	X	X	X	S
product group	group destination	wattage	dimmable	beam angle	colour temperature	fixture colour	mounting
FV Vue	H Hellion	20 20W 33 33W 45 45W	Do non-dim D1 1-10v D2 TRIAC DD DALI	40 40° 60 60°	27 2700K 30 3000K 35 3500K 40 4000K	W white B black	S surface mounted



+61 (03) 9790 8999
lighting@verbatim.com.au
www.verbatimlighting.com.au




artere 1010

flexible strip light




Small profile silicone-based flexible LED system for single colour white or red, blue, green or amber. The artere 1010 flexible strip is IP67 but can be supplied with either IP40 or IP67 connectors to suit the installation site. Either horizontal or vertical bends are available with a tight 10cm minimum bend radius. Custom layouts can be supplied with the relevant drivers and controllers to suit the specific project needs.



specifications

wattage p/m:	4.5W
bend axis:	horizontal or vertical
input voltage:	24vdc
lumens p/m:	~170lm p/m at 4.5W
CCT:	single colour 2700k up to 5700k
housing profile:	standard aluminium or recessed
IP Rating:	IP67 or IP40
IK Rating:	08

dimensional drawings



product code

catalogue number guide: Forlite artere flexible strip light

FA	H	DD	1010	10	4	DI	S
product group	bend axis	dimmable	profile (w) x (h) (mm)	length (mm)	colour temperature	connector	housing profile
FA artere	H horizontal V vertical	Do non-dim DD DALI CS Casambi	1010 10x10	10 1000	2 2700K 3 3000K 4 4000K 5 5700K	DI dual Injection Mould SI single Injection Mould SW swivel	S standard B bendable steel H hybrid R recessed



+61 (03) 9790 8999
lighting@verbatim.com.au
www.verbatimlighting.com.au



artere 1010

flexible strip light





types of connectors

1. injection-moulded connector




injection-moulded front connector (bottom)

Connects light to power supply with pre-installed bottom feed cable IP65. Available in 0.3m, 1m, 3m, 5m, 10m, 15m, 20m lengths.




injection-moulded front connector (side)

Connects light to power supply with pre-installed side feed cable IP40. Available in 0.3m, 1m, 3m, 5m, 10m, 15m, 20m lengths.




injection-moulded front connector (end)

Connects light to power supply with pre-installed end feed cable IP40. Available in 0.3m, 1m, 3m, 5m, 10m, 15m, 20m lengths.



injection-moulded end cap

Pre-installed termination protection of the light, IP40.





2. swivel connector



swivel front connector

Connects light to power supply IP40. DIY connector. Cable available in 0.3m, 1m, 3m, 5m, 10m, 15m, 20m lengths.


Feed connector with U steel plate*1 (two-pin)



swivel end cap

Termination protection of the light, IP40 DIY connector.

Tail plug with U steel plate*1



+61 (03) 9790 8999
lighting@verbatim.com.au
www.verbatimlighting.com.au



artere 1010

flexible strip light






types of connectors

1. injection-moulded connector






Injection-moulded Front Connector (bottom)

Connects light to power supply with pre-installed bottom feed cable IP65. Available in 0.3m, 1m, 3m, 5m, 10m, 15m, 20m lengths.





Injection-moulded Front Connector (side)

Connects light to power supply with pre-installed side feed cable IP40. Available in 0.3m, 1m, 3m, 5m, 10m, 15m, 20m lengths.





Injection-moulded Front Connector (end)

Connects light to power supply with pre-installed end feed cable IP40. Available in 0.3m, 1m, 3m, 5m, 10m, 15m, 20m lengths.



Injection-moulded End Cap

Pre-installed termination protection of the light, IP40.






2. swivel connector



Swivel Front Connector

Connects light to power supply IP40. DIY connector. Cable available in 0.3m, 1m, 3m, 5m, 10m, 15m, 20m lengths.



Feed connector with U steel plate*1 (two-pin)



Swivel End Cap

Termination protection of the light, IP40. DIY connector.

Tail plug with U steel plate*1



+61 (03) 9790 8999
lighting@verbatim.com.au
www.verbatimlighting.com.au



artere 1617

flexible strip light



types of connectors

1. injection-moulded connector



injection-moulded front connector (bottom)

Connection to power supply via a pre-installed bottom feed cable. IP67. Cable length available in 0.3m, 1m, 3m, 5m, 10m, 15m & 20m lengths.



injection-moulded front connector (side)

Connection to power supply via a pre-installed side feed cable IP67. Cable length available in 0.3m, 1m, 3m, 5m, 10m, 15m & 20m lengths.



injection-moulded front connector (end)

Connection power supply via a pre-installed end feed cable IP67. Cable length available in 0.3m, 1m, 3m, 5m, 10m, 15m & 20m lengths.



injection-moulded end cap

Pre-installed end cap. IP67.

2. dual injection-moulded connector



dual injection-moulded front connector (bottom)

Connection to power supply via a pre-installed bottom feed cable. IP68. Cable length available in 0.3m, 1m, 3m, 5m, 10m, 15m & 20m lengths.



dual injection-moulded front connector (side)

Connection to power supply via a pre-installed side feed cable IP68. Cable length available in 0.3m, 1m, 3m, 5m, 10m, 15m & 20m lengths.



dual injection-moulded front connector (end)

Connection power supply via a pre-installed end feed cable IP68. Cable length available in 0.3m, 1m, 3m, 5m, 10m, 15m & 20m lengths.



dual injection-moulded end cap

Pre-installed end cap. IP68.

3. snap connector



snap front connector (top end)

Connection to power supply via a DIY front connector. IP67. Cable available in 0.3m, 1m, 3m, 5m, 10m, 15m & 20m lengths.



snap front connector gside right/left

Connection to power supply via a DIY Connector. IP67. Cable available in 0.3m, 1m, 3m, 5m, 10m, 15m & 20m lengths.



snap front connector (bottom)

Connection to power supply via a DIY Connector. IP67. Cable available in 0.3m, 1m, 3m, 5m, 10m, 15m & 20m lengths.



snap end cap

DIY installed endcap. IP67.



+61 (03) 9790 8999
lighting@verbatim.com.au
www.verbatimlighting.com.au



ligne-micro

linear micro extrusion



matching miniature extrusion with quality LED boards and strips, the ligne-micro is a quality option for architectural effect lighting. Suited to retail, board-rooms or break-out spaces, the lighting designer can play with light by hiding the light source in architectural elements




family specifications


Wattages	4W, 8W, 12W, 16W
CCT	2700K, 3000K, 4000K, 6500K
luminaire output	from 600Lm to 2,500Lm
beam angle	110°
CRI	Ra80 or Ra90
lifetime	50,000hrs
IP rating	IP20
warranty	5 years

dimensional drawings


ligne 1616D



ligne 1708D



ligne 1715S



ligne 3535S



product code

product group	size	wattage	dimmable	colour temperature	fixture colour	length (mm)	mounting
FLM ligne-micro	1616 1616D	4 4W	Do non-dim	27 2700K	W white	X length in metres	SM surface mount
	1708 1708D	8 8W	D1 1-10V	30 3000K	S silver		
	1715 1715S	12 12W	DD DALI	40 4000K	B black		
	3535 3535S	16 16W	CS Casambi	65 6500K			



+61 (03) 9790 8999
lighting@verbatim.com.au
www.verbatimlighting.com.au




teso basic 15W

teso series



the teso basic series is suitable for commercial and retail applications. The clean lines of a track-recessed driver provides a clean minimalist look. And being only 52mm in diameter the Teso Basic has a low aesthetic impact. High CRI and a tight colour consistency provides a high quality lighting result to compliment any architectural project.



specifications

system wattage	15W
CCT	2700K, 3000K, 3500K, 4000K
luminaire output	nominal 810lm delivered
beam angles	15°, 25°, 40°, 60°
CRI	90
R9	50
Macadam	3 SDCM
control	on/off, DALI
track	3 circuit
lifetime	50,000hrs
build	die-cast aluminium & PC lens
IP rating	IP20
warranty	5 years
colours	black and white



product code

FT	-	B	-	15	-	x	-	x	-	x	-	x	-	T	
product group		group destination		wattage		dimmable		beam angle		cct		fixture colour		mounting	
FT	teso	B	basic	15	15W	Do	non-dim	15	15°	27	2700K	W	white	T	track
						D1	1-10V	25	25°	30	3000K	B	black		
						D2	TRIAC	40	40°	35	3500K				
						DD	DALI	60	60°	40	4000K				



+61 (03) 9790 8999
 lighting@verbatim.com.au
 www.verbatimlighting.com.au



teso basic 26W


teso series



the teso basic series is suitable for commercial and retail applications. The clean lines of a track-recessed driver provides a clean minimalist look. And being only 52mm in diameter the Teso Basic has a low aesthetic impact. High CRI and a tight colour consistency provides a high quality lighting result to compliment any architectural project.

specifications

system wattage	26W
CCT	2700K, 3000K, 3500K, 4000K
luminaire output	nominal 1200lm delivered
beam angles	15°, 25°, 40°, 60°
CRI	90
R9	50
Macadam	3 SDCM
control	on/off, DALI
track	3 circuit
lifetime	50,000hrs
build	die-cast aluminium & PC lens
IP rating	IP20
warranty	5 years
colours	black and white



product code

FT	-	B	-	26	-	x	-	x	-	x	-	x	-	T	
product group		group destination		wattage		dimmable		beam angle		cct		fixture colour		mounting	
FT	teso	B	basic	26	26W	D0	non-dim	15	15°	27	2700K	W	white	T	track
						D1	1-10V	25	25°	30	3000K	B	black		
						D2	TRIAC	40	40°	35	3500K				
						DD	DALI	60	60°	40	4000K				



+61 (03) 9790 8999
 lighting@verbatim.com.au
 www.verbatimlighting.com.au




teso pro

teso series

the teso pro range takes commercial and retail applications to the next step. The clean lines of a track-recessed driver provides a clean minimalist look. And being only 52mm in diameter the Teso Pro has a low aesthetic impact. High CRI and a tight colour consistency provides a high quality lighting result to compliment any architectural project plus the Pro has an option for a wireless controlled adjustable beam angles.

specifications

system wattage	21W		
CCT	2700K, 3000K, 3500K, 4000K		
luminaire output	nominal 1100lm delivered		
beam angles	15°, 25°, 40°, 60°		
CRI	90		
R9	50		
Macadam	3 SDCM		
control	on/off, DALI, Casambi		
track	3 circuit		
lifetime	50,000hrs		
build	die-cast aluminium & PC lens		
IP rating	IP20		
warranty	5 years		
colours	black and white		
accessories	honeycomb louvre frosted lens clear lens snoot	options	manual or casambi controlled adjustable beam



- HONEYCOMB
- CLEARLENS
- FROSTLENS



product code

FT	-	P	-	21	-	X	-	X	-	X	-	X	-	T
product group		group destination		wattage		dimmable		beam angle		cct		fixture colour		mounting
FT teso		P pro		21 21W		D0 non-dim D1 1-10V D2 TRIAC DD DALI CS Casambi		15 15° 25 25° 40 40° 60 60°		27 2700K 30 3000K 35 3500K 40 4000K		W white B black		T track




+61 (03) 9790 8999
lighting@verbatim.com.au
www.verbatimlighting.com.au




surface mount

track accessories



	black	white
FORLITE TESO TRACK SURFACE MOUNT 3 PHASE DALI 1M FORLITE TESO TRACK SURFACE MOUNT 3 PHASE DALI 2M FORLITE TESO TRACK SURFACE MOUNT 3 PHASE DALI 3M	FTTSB1 FTTSB2 FTTSB3	FTTSW1 FTTSW2 FTTSW3



	black	white
FORLITE TESO TRACK SURFACE MOUNT 3 PHASE DALI FEEDER RIGHT	FTTSBFR	FTTSWFR
FORLITE TESO TRACK SURFACE MOUNT 3 PHASE DALI FEEDER LEFT	FTTSBFL	FTTSWFL
FORLITE TESO TRACK SURFACE MOUNT 3 PHASE DALI 'L' CONNECTOR LEFT	FTTSBLL	FTTSWLL
FORLITE TESO TRACK SURFACE MOUNT 3 PHASE DALI 'L' CONNECTOR RIGHT	FTTSBLR	FTTSWLR
FORLITE TESO TRACK SURFACE MOUNT 3 PHASE DALI 'T' CONNECTOR RIGHT 1	FTTSBTR1	FTTSWTR1
FORLITE TESO TRACK SURFACE MOUNT 3 PHASE DALI 'X' CONNECTOR	FTTSBX	FTTSWX




+61 (03) 9790 8999
lighting@verbatim.com.au
www.verbatimlighting.com.au



surface mount

track accessories



	black	white
FORLITE TESO TRACK SURFACE MOUNT 3 PHASE DALI 'T' CONNECTOR RIGHT 2	FTTSBTR2	FTTSWTR2
FORLITE TESO TRACK SURFACE MOUNT 3 PHASE DALI 'T' CONNECTOR LEFT 1	FTTSBTL1	FTTSWTL1
FORLITE TESO TRACK SURFACE MOUNT 3 PHASE DALI 'T' CONNECTOR LEFT 2	FTTSBTL2	FTTSWTL2
FORLITE TESO TRACK SURFACE MOUNT 3 PHASE DALI STRAIGHT CONNECTOR	FTTSBS	FTTSWS
FORLITE TESO TRACK SURFACE MOUNT 3 PHASE DALI FLEXIBLE CONNECTOR	FTTSBF	FTTSWF
FORLITE TESO TRACK SURFACE MOUNT 3 PHASE DALI CONCEALED CONNECTOR	FTTSBC	FTTSWC




+61 (03) 9790 8999
lighting@verbatim.com.au
www.verbatimlighting.com.au




recessed mount

track accessories



	black	white
FORLITE TESO TRACK RECESSED MOUNT 3 PHASE DALI 1M FORLITE TESO TRACK RECESSED MOUNT 3 PHASE DALI 2M FORLITE TESO TRACK RECESSED MOUNT 3 PHASE DALI 3M	FTTRB1 FTTRB2 FTTRB3	FTTRW1 FTTRW2 FTTRW3



	black	white
FORLITE TESO TRACK RECESSED 3 PHASE DALI FEEDER RIGHT	FTTRBFR	FTTRWFR
FORLITE TESO TRACK RECESSED 3 PHASE DALI FEEDER LEFT	FTTRBFL	FTTRWFL
FORLITE TESO TRACK RECESSED 3 PHASE DALI 'L' CONNECTOR LEFT	FTTRBLL	FTTRWLL
FORLITE TESO TRACK RECESSED 3 PHASE DALI 'L' CONNECTOR RIGHT	FTTRBLR	FTTRWLR
FORLITE TESO TRACK RECESSED 3 PHASE DALI 'T' CONNECTOR RIGHT 1	FTTRBTR1	FTTRWTR1
FORLITE TESO TRACK RECESSED 3 PHASE DALI 'X' CONNECTOR	FTTRBX	FTTRWX




+61 (03) 9790 8999
lighting@verbatim.com.au
www.verbatimlighting.com.au



recessed mount

track accessories



	black	white
FORLITE TESO TRACK RECESSED 3 PHASE DALI 'T' CONNECTOR RIGHT 2	FTTRBTR2	FTTRWTR2
FORLITE TESO TRACK RECESSED 3 PHASE DALI 'T' CONNECTOR LEFT 1	FTTRBTL1	FTTRWTL1
FORLITE TESO TRACK RECESSED 3 PHASE DALI 'T' CONNECTOR LEFT 2	FTTRBTL2	FTTRWTL2
FORLITE TESO TRACK RECESSED 3 PHASE DALI STRAIGHT CONNECTOR	FTTRBS	FTTRWS
FORLITE TESO TRACK RECESSED MOUNT 3 PHASE DALI CONCEALED CONNECTOR	FTTRBC	FTTRWC
FORLITE TESO TRACK ENDCAP 3 PHASE DALI	FTTBE	FTTWE



+61 (03) 9790 8999
lighting@verbatim.com.au
www.verbatimlighting.com.au



cortile

stena series



the cortile is designed for general lighting applications in building exteriors and courtyards. It features a high lumen output of 125Lm/W, polycarbonate optical lens and Type III light distribution.




specifications


system wattage	20W
CCT	4000K
luminaire output	2500Lm
beam angles	90°
CRI	Ra70
control	non-dim
lifetime	50,000hrs
build	die-cast aluminium
IP rating	IP65
colour	grey
warranty	5 years

figures

dimensional drawing



light distribution: type III



product code

FC	-	20	-	Do	-	90	-	40	-	G	-	W
product group		wattage		dimmmable		beam angle		cct		fixture colour		mounting
FC cortile		20 20W		Do non-dim		90 90°		40 4000K		G grey		W wall





+61 (03) 9790 8999
lighting@verbatim.com.au
www.verbatimlighting.com.au



50d

iugis series



light source	standard	840
	optional	830 930 940 tunable white RGB RGBW
driver	standard	fixed output [non-dimmable]
	optional	DALI-2 Casambi push-dim
finishes	standard	clear anodised
	optional	white gloss powder coat black matte powder coat
lengths	standard	600 900 1200 1500 1700 2000 2300 mm [nominal]
	optional	non-standard lengths on request
bends + joins	standard	straight join t-join x-join 90° bend
	optional	custom bends custom joins
mounting	surface mount wall mount bracket wire suspended rod suspended emergency pack proximity sensor daylight sensor	

lumens / m [delivered]	1,130	1,400	1,660	2,220	2,560
wattage / m [system]	13	16	20	27	31

note

whilst every care and attention has been taken to ensure accuracy, the above technical data is intended to be used for guidance purposes only. it is not to be solely relied upon and is not to be used in place of ies files data and information subject to change without notice.





+61 (03) 9790 8999
lighting@verbatim.com.au
www.verbatimlighting.com.au



50di

iugis series



light source	standard	840 [direct + indirect]
	optional	830 930 940 tunable white RGB RGBW [direct + indirect]
driver	standard	fixed output [non-dimmable]
	optional	DALI-2 Casambi push-dim
finishes	standard	clear anodised
	optional	white gloss powder coat black matte powder coat
lengths	standard	600 900 1200 1500 1700 2000 2300 mm [nominal]
	optional	non-standard lengths on request
bends + joins	standard	straight join t-join x-join 90° bend
	optional	custom bends custom joins
mounting	wall mount bracket wire suspended rod suspended emergency pack proximity sensor daylight sensor	

lumens / m [delivered]	1,130	1,400	1,660	2,220	2,560
wattage / m [system]	13	16	20	27	31

note

whilst every care and attention has been taken to ensure accuracy, the above technical data is intended to be used for guidance purposes only. it is not to be solely relied upon and is not to be used in place of ies files data and information subject to change without notice.




+61 (03) 9790 8999
lighting@verbatim.com.au
www.verbatimlighting.com.au



50r

iugis series



light source	standard	840
	optional	830 930 940 tunable white RGB RGBW
driver	standard	fixed output [non-dimmable]
	optional	DALI-2 Casambi push-dim
finishes	standard	clear anodised
	optional	white gloss powder coat black matte powder coat
lengths	standard	600 900 1200 1500 1700 2000 2300 mm [nominal]
	optional	non-standard lengths on request
bends + joins	standard	straight join t-join x-join 90° bend
	optional	custom bends custom joins
mounting	recessed into wall or ceiling emergency pack proximity sensor daylight sensor	

lumens / m [delivered]	1,130	1,400	1,660	2,220	2,560
wattage / m [system]	13	16	20	27	31

note

whilst every care and attention has been taken to ensure accuracy, the above technical data is intended to be used for guidance purposes only. it is not to be solely relied upon and is not to be used in place of ies files data and information subject to change without notice.





+61 (03) 9790 8999
lighting@verbatim.com.au
www.verbatimlighting.com.au



60d

iugis series



light source	standard	840
	optional	830 930 940 tunable white RGB RGBW
driver	standard	fixed output [non-dimmable]
	optional	DALI-2 Casambi push-dim
finishes	standard	clear anodised
	optional	white gloss powder coat black matte powder coat
lengths	standard	600 900 1200 1500 1700 2000 2300 mm [nominal]
	optional	non-standard lengths on request
bends + joins	standard	straight join t-join x-join 90° bend
	optional	custom bends custom joins
mounting	surface mount wall mount bracket wire suspended rod suspended emergency pack proximity sensor daylight sensor	

lumens / m [delivered]	1,170	1,450	1,720	2,300	2,650
wattage / m [system]	13	16	20	27	31

note

whilst every care and attention has been taken to ensure accuracy, the above technical data is intended to be used for guidance purposes only. it is not to be solely relied upon and is not to be used in place of ies files data and information subject to change without notice





+61 (03) 9790 8999
lighting@verbatim.com.au
www.verbatimlighting.com.au



6odi

iugis series



light source	standard	840 [direct + indirect]
	optional	830 930 940 tunable white RGB RGBW [direct + indirect]

driver	standard	fixed output [non-dimmable]
	optional	DALI-2 Casambi push-dim

finishes	standard	clear anodised
	optional	white gloss powder coat black matte powder coat

lengths	standard	600 900 1200 1500 1700 2000 2300 mm [nominal]
	optional	non-standard lengths on request

bends + joins	standard	straight join t-join x-join 90° bend
	optional	custom bends custom joins

mounting	standard	wall mount bracket wire suspended rod suspended
	optional	emergency pack proximity sensor daylight sensor

lumens / m [delivered]	1,170	1,450	1,720	2,300	2,560
wattage / m [system]	13	16	20	27	31

note

whilst every care and attention has been taken to ensure accuracy, the above technical data is intended to be used for guidance purposes only. it is not to be solely relied upon and is not to be used in place of ies files data and information subject to change without notice





+61 (03) 9790 8999
lighting@verbatim.com.au
www.verbatimlighting.com.au



75d

iugis series



light source	standard	840
	optional	830 930 940 tunable white RGB RGBW
driver	standard	fixed output [non-dimmable]
	optional	DALI-2 Casambi push-dim
finishes	standard	clear anodised
	optional	white gloss powder coat black matte powder coat
lengths	standard	600 900 1200 1500 1700 2000 2300 mm [nominal]
	optional	non-standard lengths on request
bends + joins	standard	straight join t-join x-join 90° bend
	optional	custom bends custom joins
mounting	surface mount wall mount bracket wire suspended rod suspended emergency pack proximity sensor daylight sensor	

lumens / m [delivered]	1,290	1,600	1,900	2,530	2,920
wattage / m [system]	13	16	20	27	31

note

whilst every care and attention has been taken to ensure accuracy, the above technical data is intended to be used for guidance purposes only. it is not to be solely relied upon and is not to be used in place of ies files data and information subject to change without notice.





+61 (03) 9790 8999
lighting@verbatim.com.au
www.verbatimlighting.com.au



75di

iugis series



light source	standard	840 [direct + indirect]
	optional	830 930 940 tunable white RGB RGBW [direct + indirect]
driver	standard	fixed output [non-dimmable]
	optional	DALI-2 Casambi push-dim
finishes	standard	clear anodised
	optional	white gloss powder coat black matte powder coat
lengths	standard	600 900 1200 1500 1700 2000 2300 mm [nominal]
	optional	non-standard lengths on request
bends + joins	standard	straight join t-join x-join 90° bend
	optional	custom bends custom joins
mounting	wall mount bracket wire suspended rod suspended emergency pack proximity sensor daylight sensor	

lumens / m [delivered]	1,290	1,600	1,900	2,530	2,920
wattage / m [system]	13	16	20	27	31

note

whilst every care and attention has been taken to ensure accuracy, the above technical data is intended to be used for guidance purposes only. it is not to be solely relied upon and is not to be used in place of ies files data and information subject to change without notice.




+61 (03) 9790 8999
lighting@verbatim.com.au
www.verbatimlighting.com.au



75r

iugis series



light source	standard	840
	optional	830 930 940 tunable white RGB RGBW
driver	standard	fixed output [non-dimmable]
	optional	DALI-2 Casambi push-dim
finishes	standard	clear anodised
	optional	white gloss powder coat black matte powder coat
lengths	standard	600 900 1200 1500 1700 2000 2300 mm [nominal]
	optional	non-standard lengths on request
bends + joins	standard	straight join t-join x-join 90° bend
	optional	custom bends custom joins
mounting	recessed into wall or ceiling emergency pack proximity sensor daylight sensor	

lumens / m [delivered]	1,290	1,600	1,900	2,530	2,920
wattage / m [system]	13	16	20	27	31

note

whilst every care and attention has been taken to ensure accuracy, the above technical data is intended to be used for guidance purposes only. it is not to be solely relied upon and is not to be used in place of ies files data and information subject to change without notice.



+61 (03) 9790 8999
lighting@verbatim.com.au
www.verbatimlighting.com.au





contact

address: Unit 6, 450 Princes Highway,
Noble Park, VIC 3174

phone: +61 (03) 9790 8999

email: lighting@verbatim.com.au

web: verbatimlighting.com.au

 [linkedin.com/company/verbatimlighting](https://www.linkedin.com/company/verbatimlighting)

 [facebook.com/VerbatimlightingAU](https://www.facebook.com/VerbatimlightingAU)

 [instagram.com/verbatimlightingau](https://www.instagram.com/verbatimlightingau)