

quantum IP65

vue series




the quantum uses a narrow aperture body to project light across a wide area while limiting glare. trim options of black or white and a reflector in black provide a smooth transition from ceiling to light source. IP65 rated version make it suitable to use in wet areas.

the quantum has a simple yet elegant design and the blend of quality components and high-CRI light sources elevates the quantum above the pack. the quantum IP65 is supplied with a remote driver (IP20 unless requested otherwise requested).



specifications

system wattage:	10W, 20W, 30W
luminaire output:	800lm (10W), 1300lm (20W), 2150lm (30W)
CCT:	2700K, 3000K, 4000K, 5000K
optics:	15°, 30°, 45°
CRI:	>90
control:	non-dim, 1-10V, Triac, DALI, Casambi
operating voltage:	240Vac
finish:	white, black
housing:	aluminium and PC
diffuser:	high transparency optical lens
enclosure protection:	IP65
operating temp:	25°C
lifetime:	40,000hrs
warranty:	5 years
accessories:	N/A



product code

FV	QW	X	X	X	X	X	R
product group	group designation	wattage	dimmable	beam angle	cct	fixture colour	mounting
FV vue	QW quantum IP65	10 10W 20 20W 30 30W	Do non-dim D1 1-10V D2 TRIAC DD DALI CS Casambi	15 15° 30 30° 45 45°	27 2700K 30 3000K 35 3500K 40 4000K	W white B black	R recessed



+61 (03) 9790 8999
lighting@verbatim.com.au
www.verbatimlighting.com.au

